



## CAIROX® POTASSIUM PERMANGANATE FREE-FLOWING GRADE

CAS Registry No. 7722-64-7 Municipal Drinking Water Data Sheet

Free-Flowing grade is recommended where potassium permanganate is subjected to high humidity conditions and where the material is to be dry fed through a chemical feeder or stored in a bin or hopper.

### TECHNICAL GRADE

#### Assay

Guaranteed 97%  $\text{KMnO}_4$

#### Particle Size

20% maximum retained on #425 micron  
(formerly #40 U.S. Standard Sieve )

7% maximum through #75 micron  
(formerly #200 U.S. Standard Sieve)

#### Standards & Specifications

CAIROX® potassium permanganate is certified by the National Sanitation Foundation (NSF) to NSF/ANSI Standard 60: Drinking Water Treatment Chemicals – Health Effects

#### Free-Flowing grade meets:

AWWA Standard B603

NSF Maximum Use Level 50 mg/L



### CHEMICAL/PHYSICAL DATA

<b>Formula:</b>	$\text{KMnO}_4$
<b>Formula Weight:</b>	158.0 g/mol
<b>Form:</b>	Granular Crystalline
<b>Specific Gravity:</b>	
Solid	2.703 g/cm <sup>3</sup>
3% Solution	1.020 g/mL by weight, 20°C/4°C
<b>Bulk Density:</b>	Approximately 100 lb/ft <sup>3</sup>
<b>Decomposition:</b>	May start at 150°C/302°F

### SOLUBILITY IN DISTILLED WATER

TEMPERATURE		SOLUBILITY	
°C	°F	g/L	oz/gal
0	32	27.8	3.7
20	68	65.0	8.6
40	104	125.2	16.7
60	140	230.0	30.7
70	158	286.4	38.3
75	167	323.5	43.2

### DESCRIPTION

Crystals or granules are dark purple with a metallic sheen, sometimes with a dark bronze-like appearance. Potassium permanganate has a sweetish, astringent taste and is odorless.

### HANDLING, STORAGE & INCOMPATIBILITY

Protect containers against physical damage. When handling potassium permanganate, respirators should be worn to avoid irritation of or damage to mucous membranes. Eye protection should also be worn when handling potassium permanganate as a solid or in solution.

Potassium permanganate is stable and will keep indefinitely if stored in a cool, dry area in closed containers. Concrete floors are preferred to wooden decks. To clean up spills and leaks, follow the steps recommended in the Safety Data Sheet (SDS). Be sure to use goggles, rubber gloves, and respirator when cleaning up a spill or leak.

Avoid contact with acids, peroxides, and all combustible organic or readily oxidizable materials including inorganic oxidizable materials and metal powders. With hydrochloric acid, chlorine gas is liberated. Potassium permanganate is not combustible, but will support combustion. It may decompose if exposed to intense heat. **Fires may be controlled and extinguished by using large quantities of water. Refer to the SDS for more information.**

### APPLICATIONS

Listed below are some of the many applications of potassium permanganate. Permanganate is a powerful oxidizing agent. The optimum condition under which it is to be used can be easily established through technical service evaluations or laboratory testing.

- Oxidation & Synthesis
- Water Treatment
- Municipal Wastewater Treatment
- Industrial Wastewater Treatment
- Metal Surface Treatment
- Equipment Cleaning
- Purification of Gases
- Mining & Metallurgical
- Slag Quenching
- Food Processing



## SHIPPING

CAIROX® potassium permanganate is classified and listed as an oxidizer by PHMSA (Pipeline and Hazardous Materials Safety Administration, Department of Transportation, in 49 CFR Subchapter C, HMR (Hazardous Materials Regulation), Part 172.101 HMT (Hazardous Materials Table). It is shipped under Interstate Commerce Commission's (ICC) Tariff 19.

**Proper Shipping Name:** Potassium Permanganate (RQ-100/45.4)  
**Hazard Class:** Oxidizer  
**Identification Number:** UN 1490  
**Label Requirements:** Oxidizer  
**Packaging Requirements:** 49 CFR Parts 100 to 199

## SHIPPING CONTAINERS

**25 kg pail<sup>(1)</sup> (55.125 lb.) net**, with handle, made of HDPE, weighs 2.7 lbs. (1.22 kg). It is tapered to allow nested storage of empty drums, stands approximately 15.6 in. (39.7 cm) high and has a maximum diameter of 12.3 in. 31.2 cm).

**150 kg drum<sup>(1)</sup> (330.75 lb.) net**, made of 22-gauge steel, weighs 25.3 lbs. (11.5 kg). It stands approximately 28.4 in. (72.2 cm) high and is approximately 19.7 in. (50.0 cm) in diameter.

**1500 kg CYCLE BIN™<sup>(2)</sup> reusable container (3307 lb.) net**

**Bulk up to 48,000 lbs.**

**Packaging Weight Tolerance +/- 1%**

Other containers may be available.  
Contact Carus at (800) 435-6856 for details.

(1) Meets UN performance oriented packaging requirements  
(2) The CYCLE BIN meets DOT 56 or UN 11A Specifications.

## CORROSIVE PROPERTIES

Potassium permanganate is compatible with many metals and synthetic materials. Natural rubbers and fibers are often incompatible. Solution pH and temperature are also important factors. The material must be compatible with either the acid or alkali also being used.

In neutral and alkaline solutions, potassium permanganate is not corrosive to iron, mild steel, or stainless steel; however, chloride corrosion of metals may be accelerated when an oxidant such as permanganate is present in solution. Plastics such as polypropylene, polyvinyl chloride Type I (PVC I), epoxy resins, fiberglass reinforced plastic (FRP), Penton, Lucite®, Viton™ A, and Hypalon are suitable. Teflon™ FEP and TFE, and Tefzel™ ETFE are best. **Refer to Material Compatibility Chart.**

Aluminum, zinc, copper, lead, and alloys containing these metals may be (slightly) affected by potassium permanganate solutions. **Actual studies should be made under the conditions in which permanganate will be used.**

## REPACKING

When potassium permanganate is repacked, the packing, markings, labels, and shipping conditions must meet applicable federal regulations. See Code of Federal Regulations-49, Transportation (parts 100-199) and Federal Hazardous Materials Substances Act, 15 U.S.C. 1261.

Permanganate products are not registered as a pesticide under the Federal Insecticide, Fungicide and Rodenticide Act administered by U.S. EPA or similar state laws. Use as a pesticide is not government approved.



### Carus Headquarters USA

315 Fifth Street | Peru, IL 61354 | Tel +1 (815) 223-1500 | 1(800) 435-6856 | Fax +1 (815) 224-6697  
carusllc.com | salesmkt@carusllc.com

### Carus Europe

Calle Rosal 4, 1-B | Oviedo, Spain 33009 | Tel +34.985.785.513 | Fax +34.985.785.510

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change; and the conditions of handling, use or misuse of the product are beyond our control. Carus makes no warranty, either expressed or implied, including any warranties of merchantability and fitness for a particular purpose. Carus also disclaims all liability for reliance on the completeness or confirming accuracy of any information included herein. Users should satisfy themselves that they are aware of all current data relevant to their particular use(s).

Carus and Design is a registered service mark of Carus. CAIROX® is a registered trademark of Carus.  
Responsible Care® is a registered service mark of the American Chemistry Council.



**RESPONSIBLE CARE™**  
Driving Safety & Sustainability

© 2024 Carus. All Rights Reserved.  
Rev. 12/2024