



CARUSOL® C LIQUID PERMANGANATE

CAS Registry No. 10101-50-5 EINECS Reference No. 233-251-1 Municipal Drinking Water Data Sheet

CARUSOL C liquid permanganate is an effective oxidant recommended for potable drinking water applications that require a concentrated permanganate solution. Applications include iron and manganese reduction, taste and odor control, disinfection by-product reduction, color reduction, and radium reduction.

PRODUCT SPECIFICATIONS

Assay:	39.5–41.0% as NaMnO ₄
pH:	5.0–8.0
Solubility in Water:	Miscible with water in all proportions

Standards & Specifications:

CARUSOL C meets:

AWWA Standard B603-10

EN: 15482-10 mg/L max

ANSI/NSF 60

NSF Maximum Use Level 88 mg/L

KIWA- Product certification no. K83927-8 mg/L max



Certified to
NSF/ANSI/CAN 60



CHEMICAL/PHYSICAL DATA

Formula:	NaMnO ₄
Appearance:	Dark Purple Solution
Specific Gravity:	1.36–1.39
Freezing Point:	5° F (-15° C)

APPLICATIONS

- Drinking Water Purification
- Iron/Manganese Oxidation
- Taste & Odor Control
- Preoxidant for THM & HAA Control
- Radium Removal
- Color Removal

BENEFITS

- Concentrated liquid oxidant
- More precise dosing of chemical
- Feed equipment is simplified
- Consistent concentration

HANDLING, STORAGE & COMPATIBILITY

Like any strong oxidant, CARUSOL C liquid permanganate should be handled with care. Protective equipment during handling should include face shields and goggles, rubber or plastic gloves, and a rubber or plastic apron. If has come into contact with sodium permanganate, wash off immediately; spontaneous ignition can occur with cloth or paper. In cases where significant exposure exists, use of the appropriate NIOSH/MSHA dust or mist respirator is recommended.

Store in accordance with NFPA (National Fire Protection Association) Code 400 Hazardous Materials Code, Chapter 15 - Oxidizer Solids and Liquids. The product should be stored in a cool, dry area in closed containers. Concrete floors are preferred. Avoid wooden decks. Spillage should be collected and disposed of properly. Contain and dilute spillage to approximately 6% with water, and then reduce with sodium thiosulfate, a bisulfite, or ferrous salt solution. The bisulfite or ferrous salt may require some dilute sulfuric acid (10% w/w) to promote reduction. Neutralize with sodium carbonate to neutral pH, if acid was used. Deposit sludge in an approved landfill or, where permitted, drain into sewer with large quantities of water.

As an oxidant, the product itself is non-combustible but will accelerate the burning of combustible materials. Therefore, contact with all combustible materials and/or chemicals must be avoided. These include but are not limited to: wood, cloth, organic chemicals, and charcoal. Avoid contact with acids, peroxides, metal powders, sulfites, oxalates, and all other oxidizable inorganic chemicals. Contact with sulfuric acid, peroxides, or metal powders may result in an explosion. During contact with hydrochloric acid, chlorine gas is liberated. Additionally, avoid contact with reducing agents (e.g., sulfites, oxalates, etc.) as they can cause violent reactions. **Consult the Safety Data Sheet (SDS) for additional safety information.**



HANDLING, STORAGE & COMPATIBILITY

CARUSOL® C liquid permanganate is compatible with many metals and synthetic materials. Natural rubbers and fibers are often incompatible. Solution pH and temperature are also important factors. The material selected for use with liquid permanganate must also be compatible with any kind of acid or alkali being used.

In neutral and alkaline solutions, sodium permanganate is not corrosive to carbon steel and 316 stainless steel; however, chloride corrosion of metals may be accelerated when an oxidant such as liquid permanganate is present in solution.

Aluminum, zinc, copper, lead, and alloys containing these metals may be (slightly) affected by liquid permanganate solutions. Actual corrosion or compatibility studies should be made under the conditions in which permanganate will be used prior to use.

SHIPPING

CARUSOL C liquid permanganate is classified and listed as an oxidizer by PHMSA (Pipeline and Hazardous Materials Safety Administration), Department of Transportation, in 49 CFR Subchapter C, HMR (Hazardous Materials Regulation), Part 172.101 HMT (Hazardous Materials Table).

Proper Shipping Name: Permanganates, inorganics, aqueous solution n.o.s.
(contains sodium permanganate).

Hazard Class: 5.1

Identification Number: UN 3214

Packaging Group: II

Label Requirements: Oxidizer, 5.1

SHIPPING CONTAINERS

5 gallon (20-L) Jerrican (UN Specification: UN3H1/ Y1.8/100)
Made of high density polyethylene (HDPE). Weighs 3.3 lbs. (1.5 kg). The jerrican stands approximately 13.4 inches (33.9 cm) tall, 9.4 inches (23.8 cm) wide, and 13.0 inches (33.0 cm) deep. The net weight is 57 lbs. (25.8 kg).

55 gallon drum (208 L) (UN Specification: UN1H1/Y 1.9/100)
Made of high density polyethylene (HDPE), weighs 22 lbs. (10 kg). The drum stands approximately 34.8 inches (88.3 cm) tall, has an outside diameter of 23.3 inches (59.2 cm). The net weight is 550 lbs. (250 kg). (Domestic and International)

275 gallon (1041 L) IBC (Intermediate Bulk Container)
(UN Specification: UN31HA1/Y1.9/100) Weighs 139 lbs. (65 kg). The IBC contains 263 gallons of product. The IBC dimensions are 45.4 inches high, 48 inches long, and 40 inches wide. The IBC has a 2 inch butterfly valve with NPT threads in bottom sump. The net weight is 3,000 lbs. (1360 kg).

Bulk Shipping Quantities from 3000–3800 gallons are available.

Permanganate products are not registered as a pesticide under the Federal Insecticide, Fungicide and Rodenticide Act administered by U.S. EPA or similar state laws. Use as a pesticide is not government approved.



Carus Headquarters USA

315 Fifth Street | Peru, IL 61354 | Tel +1 (815) 223-1500 | 1(800) 435-6856 | Fax +1 (815) 224-6697
carusllc.com | salesmkt@carusllc.com

Carus Europe

Calle Rosal 4, 1-B | Oviedo, Spain 33009 | Tel +34.985.785.513 | Fax +34.985.785.510

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change; and the conditions of handling, use or misuse of the product are beyond our control. Carus makes no warranty, either expressed or implied, including any warranties of merchantability and fitness for a particular purpose. Carus also disclaims all liability for reliance on the completeness or confirming accuracy of any information included herein. Users should satisfy themselves that they are aware of all current data relevant to their particular use(s).

Carus and Design is a registered service mark of Carus. CARUSOL® is a registered trademark of Carus.
Responsible Care® is a registered service mark of the American Chemistry Council.



RESPONSIBLE CARE®
Driving Safety & Sustainability